

NEW MANGALORE PORT AUTHORITY

Mechanical Engineering Department Panambur, Mangalore - 575 010

Phone: 0824 - 2887730

No. 20/114/2022-23/EE(M)III/TS(OTM)

Date: 08/02/2023

To,

Intended Bidders

Sir,

Sub: Testing of Aqueous Film Forming Foam (AFF Foam) compound sample of Fire Fighting System of Oil Jetty No.10, 11, 12 & 13 of NMPA - Budgetary Quotations Requested - Reg.

Budgetary quotations are invited for "Testing of Aqueous Film Forming Foam (AFFF) compound sample of Fire Fighting System of Oil Jetty No.10,11,12& 13 of NMPA" as per Bill of Quantity and Terms & conditions detailed below:

Bill of Quantity

SI.	Description of testing	Quantity	Rate in Rs.	Amount in Rs
No.			-	4
1	Testing of Aqueous Film Forming	05		
	Foam (AFF Foam) compound	samples	1	
	sample of Fire Fighting System of	я •		
	Oil Jetty No.10, 11, 12 & 13 of			x ž
	NMPA to conform to the physical		1	
	requirements as per Clause No.		Ī.	
	5.3.3 of OISD-GDN-115 (extract			,
	of Clause No. 5.3.3 of OISD-GDN-		12	
	115, is enclosed as Annexure .A)			
	GST @			
	Grand Total			

(Rupees		Only
• • • • • • • • • • • • • • • • • • • •		-

Terms & Condition:

- 1. The rate quoted shall be firm & final inclusive of all taxes & duties excluding GST.
- 2. GST as applicable shall be paid extra. GST shall be quoted separately.

- 3. GST Certificate shall be enclosed along with the quotation. The firm shall submit the copy of GST Certificate along with the quotation. If GST certificate is not produced, the quotation shall not be considered for evaluation.
- 4. No escalation in price whatsoever will be allowed till completion of the work.
- 5. The rate quoted should be valid for at least 45 days from the due date of submission of offer.
- 6. Testing of Aqueous Film Forming Foam (AFF Foam) compound sample of Fire Fighting System of Oil Jetty No.10, 11, 12 & 13 of NMPA to be done to conform to the physical requirements as per Clause No. 5.3.3 of OISD-GDN-115 (extract of Clause No. 5.3.3 of OISD-GDN-115, is enclosed as Annexure .A for reference). The certificate of qualified laboratory having testing facilities for quality condition testing of AFF Foam compound shall be enclosed to the enquiry letter. If the certificate is not produced, the quotation shall not be considered for evaluation.
- 7. Five samples (1 to 2 Litres each) of AFF Foam compound in cans with identification marking, will be sent to the laboratory of the successful bidder for testing and the sample to be tested as per Clause No. 5.3.3 of OISD-GDN-115 and test reports to be submitted to the undersigned within 20 days from the date of receipt of sample at the laboratory of the firm.
- 8. Payment will be made within 15 days from the date of receipt of bills and test reports.
- 9. Statutory Taxes as applicable will be deducted while releasing the payment.

The budgetary quotations enclosed in a sealed cover super scribed as "Testing of Aqueous Film Forming Foam (AFF Foam) compound sample of Fire Fighting System of Oil Jetty No.10, 11, 12 & 13 of NMPA" should reach to the under signed on or before 20/02/2023 at 15:00 Hrs. to the below mentioned address. Budgetary Quotations will be opened on the same day at 4.00 PM.

Thanking you,

(Krishnamurthy D S

Executive Engineer (M)III NMPA, Panambur

13 60

Address for Communication:

Executive Engineer (M)III,

Administrative Building, 2nd Floor, Room No.234,

New Mangalore Port Authority,

Panambur, Mangalore - 575010.

Mob: 9449700435, Ph: 0824 - 2887730 Email: krishnamurthy.ds@nmpt.gov.in



OISD = GDN = 115

GUIDELINES ON FIRE FIGHTING, EQUIPMENT AND APPLIANCES IN PETROLEUM INDUSTRY

9r:Number 0180/000/2012/018

Page No. 44

5.3.3 CONCENTRATE CHARASTERASTICS

The concentrate should conform to the physical requirements as below

Concentrate requirements	Values		
	Max, Min		
Viscosity, at 27 ± 1 deg. C (Centistokes)	40		
Hydrogen ion concentration (pH) for both original and conditioned sample.	75 to 7		
Specific Gravity for both original & conditioned	11	Ĭ.O	
sample		V	
Miscibility with water /sea water	w Mariol		
Sludge contents (% viv)	0.25%		
Freezing Point	Should flow	at '5°C	
Film Formation	Forms Aqueous Film		1
Spreading coefficient	, j	45	
Expansion at 27±1 o C	12	8	
25% drainage time at 27±1oC		90 Sec	
Fire test extinction time	60 Sec	•	
Resistance to burn back (thermal stability)		8 Min	

Storage

- The concentrate should have shelf life as per relevant indian Standard.
- The foam compound should be tested every 3 years at random.

Homogeneity

The concentrate should be homogeneous. No solidification or separation of crystals or stratification should take place.

Compatibility

The foam produced from the concentrate should be compatible with dry chemical powder.

"OISD hereby expressly disclaims any liability or responsibility for loss or damage resulting from the use of OISD Standards/Guidelines."

18 6