नव मेंगलोर पत्तन प्राधिकरण / NEW MANGALORE PORT AUTHORITY

सिविल एंगिनीरिंग विभग / DEPARTMENT OF CIVIL ENGINEERING अनुरक्षन प्रभाग –I / MAINTENANCE DIVISION-I

कोटेशन /QUOTATION No.5/401/CIVIL/Mtc-I/2025-TS dated 16.06.2025

कोटेशन आमंत्रित किए जाते हैं निम्नलिखित कार्य के लिए प्रतिष्ठित एवं अनुभवी ठेकेदारों या फर्म से प्रतिशत दर के आधार पर मुहरबंद

contractors for the following work; Sealed quotations are invited on percentage rate basis from the reputed and experienced

काये का नाम;

Name of work

अनुमानित लागत /Estimated Cost

ईएमडी /EMD खुलने की तिथि /Date of opening सेमापन अवधि /Completion Period

: एल्युमिनियम कम्पोजिट पैनल (एसीपी) छत प्रदान करके एनएमपीए गेस्ट हाउस के प्रवेश लॉबी का विस्तार

providing Aluminium Composite Panel (ACP) roofing : Extension of entrance lobby of NMPA Guest House by

23.06.2025

the bidders or their authorized representatives. The BOQ, specification and other particulars are enclosed. The NMPA reserves the right to accept or reject quotation without assigning reasons before 3.00 P.M. on 23.06.2025 and will be opened at 3.30P.M on the same day in the presence of The quotation shall be dropped in the tender box placed in A.O. building ground floor on or

of receipt of RTGS/NEFT/Certificate will not be entertained. MSE registered with District Industries Centers (DIC) shall be enclosed. The quotation without copy exemption of EMD to all Micro and Small Enterprises (MSE) shall be allowed. The proof of being and copy of the NEFT/RTGS receipt shall be enclosed along with the quotation. The benefit of The Earnest Money Deposit shall be paid through NEFT/RTGS in favour of FA&CAO, NMPA

1. Name of the Bank: NMPA Bank Details for remittance of Tender fee and EMD.

Name of the Bank: State Bank of India, Panambur, Mangalore - 575 010

2.Bank A/C No. 10205649448

SBIN0002249

4.MICR Code: 575002011

enclosed BOQ. The percentage rate quoted shall be inclusive of labour, tool and made after satisfactory completion of work and applicable taxes will be recovered from the bill. transportation, machinery etc. complete. GST will be reimbursed as applicable. Payment will be The Contractor shall write the percentage rate in figures as well as in words clearly in the

agreement/undertaking in the prescribed form on a stamp paper of required value and sign all the pages of the contract form including Plan(s) enclosed to the same letter head having GST/Pan. The offer submitted should be open for acceptance for a period of 90 The Contractor shall submit the quotation accompanied with covering letter on bidder's date of opening the same. The successful bidder shall

कार्यकारी अभियंता (सिविल) / Executive Engineer (Civil), रखरखाव प्रभाग-1 / Maintenance Division-I,

Date: 24.06.2025

3.00P.M n 27.06.2025 The above subject work will be extend upto 27.06.2025 and submission on or before Show

कार्यकारी अभियंता (सिविल) / Executive Engineer (Civil), रखरखाव प्रभाग-I / Maintenance Division-I,

नव मेंगलोर पत्तन प्राधिकरण / NEW MANGALORE PORT AUTHORITY कोटेशन/QUOTATION No.5/401/CIVIL/Mtc-I/2025-TS dated 16.06.2025 सिविल एंगिनीरिंग विभग / DEPARTMENT OF CIVIL ENGINEERING अनुरक्षन प्रभाग –I / MAINTENANCE DIVISION-I

BILL OF QUANTITIES

कार्य का नाम: एल्युमिनियम कम्पोजिट पैनल (एसीपी) छत प्रदान करके एनएमपीए गेस्ट हाउस के प्रवेश लॉबी का विस्तार Name of work: Extension of entrance lobby of NMPA Guest House by providing

	S	Aluminium Composite Panel (ACP) roofing	l (ACP) roo	fing	Survivors of Survivors	
Providing and fabricating G.I. section of required pattern in frames with rectangular hollow G.I. Sections, etc. including priming coat with approved steel primer all complete. Fixed to openings with necessary fixtures and fittings etc. complete. Sections, etc. other of the GI sections. The panel should composite panel of approved nake and colour for roofing at required level fixed to the GI sections. The panel should consist of 3mm thick non-halogenated FR grade mineral based polymer (2 hrs fire resistance as per ASTM E119-12 and clause B, S1, do as per ENT13501-1 sandwiched between 0.50 skins thick aluminium sheet making a total panel thickness of 4mm. The surfaces will be finished with PVDF based coating on reverse sides would be in polysester paint. The system shall be fixed using GI brackets, aluminium L cleats selfshreading screws and stainless steel bolts and nuts complete with spring washer and cap nuts and all other necessarys etc. Finishing with Epoxy paint (two coats) at all locations prepared and applied as per manufacturer's specifications including appropriate priming coat, preparation of surface, etc. complete. On steel work including preparing of materials, labour complete as per specifications and as per directions of Enginer-in-charge.	Z		Qty	Unit	Rate in	Amo
required pattern in frames with rectangular hollow GJ. Sections, etc. including priming coat with approved steel primer all complete. Fixed to openings with necessary fixtures and fittings etc. complete. Providing and fixing of Aluminium composite panel of approved make and colour for roofing at required level fixed to the GJ sections. The panel should consist of 3mm thick non-halogenated FR grade mineral based polymer (2 hrs fire resistance as per ASTM E119-12 and clause B, S1, do as per ENV13601-1 sandwiched between 0.50 skins thick aluminium sheet making a total panel thickness of 4mm. The surfaces will be finished with PVDF based coating on top sides would be in polyester paint. The system shall be fixed using GI brackets, aluminium L cleats steel bolts and nuts complete with spring washer and cap nuts and all other necessarys etc. Complete Finishing with Epoxy paint (two coats) at all locations prepared and applied as per manufacturer's specifications including appropriate priming coat, preparation of surface, etc. complete. On steel work including preparing the surface after thoroughy cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per directions of Enginer-in-charge.	-		300.00	Kρ	166 75	RS.
steel primer all complete. Fixed to openings with necessary fixtures and fittings etc. complete. Providing and fixing of Aluminium composite panel of approved make and colour for roofing at required level fixed to the GI sections. The panel should consist of 3mm thick non-halogenated FR grade mineral based polymer (2 hrs fire resistance as per ASTM E119-12 and clause B, S1, do as per ENT13501-1sandwiched between 0.50 skins thick aluminium sheet making a total panel thickness of 4mm. The surfaces will be finished with PVDF based coating on top sides and service coating on reverse sides would be in polyester paint. The system shall be fixed using GI brackets, aluminium L cleats/ selfthreading screws and stainless steel bolts and nuts complete with spring washer and cap nuts and all other necessarys etc. Finishing with Epoxy paint (two coats) at all locations prepared and applied as per manufacturer's specifications including appropriate priming coat, preparation of surface, etc. complete. On steel work including preparing the surface after thorougly cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.		required pattern in frames with rectangular hollow G.I. Sections, etc.		o		0,0
openings with necessary fixtures and fittings etc. complete. Providing and fixing of Aluminium 56.00 Sqm 1930.34 composite panel of approved make and colour for roofing at required level fixed to the GI sections. The panel should consist of 3mm thick non-halogenated FR grade mineral based polymer (2 hrs fire resistance as per ASTM E119-12 and clause B, S1, do as per EMT13501. Isandwiched between 0.50 skins thick aluminium sheet making a total panel thickness of 4mm. The surfaces will be finished with PVDF based coating on reverse sides would be in polyester paint. The system shall be fixed using GI brackets, aluminium L cleats/ selfthreading screws and stainless steel bolts and nuts complete with spring washer and cap nuts and all other necessarys etc. Finishing with Epoxy paint (two coats) at all locations prepared and applied as per manufacturer's specifications including preparing the surface after thoroughy cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.		including priming coat with approved steel primer all complete. Fixed to				
fittings etc. complete. Providing and fixing of Aluminium 56.00 Sqm 1930.34 composite panel of approved make and colour for roofing at required level fixed to the GI sections. The panel should consist of 3mm thick non-halogenated FR grade mineral based polymer (2 hrs fire resistance as per ASTM E119-12 and clause B, S1, do as per ENT13501-15 and which end between 0.50 skins thick aluminium sheet making a total panel thickness of 4mm. The surfaces will be finished with PVDF based coating on reverse sides would be in polyester paint. The system shall be fixed using GI brackets, aluminium L cleats/ selfthreading screws and stainless steel boits and nuts complete with spring washer and cap nuts and all other necessarys etc. Finishing with Epoxy paint (two coats) at all locations prepared and applied as per manufacturer's specifications including preparing the surface, etc. complete. On steel work including preparing the surface after thoroughy cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.		openings with necessary fixtures and				
Providing and fixing of Aluminium composite panel of approved make and colour for roofing at required level fixed to the GI sections. The panel should consist of 3mm thick non-halogenated FR grade mineral based polymer (2 hrs fire resistance as per ASTM £119-12 and clause B, S1, do as per ENT13501-15 landwiched between 0.50 skins thick aluminium sheet making a total panel thickness of 4mm. The surfaces will be finished with PVDF based coating on reverse sides would be in polyester paint. The system shall be fixed using GI brackets, aluminium L cleats/ selfthreading screws and stainless steel bolts and nuts complete with spring washer and cap nuts and all other necessarys etc. Finishing with Epoxy paint (two coats) at all locations prepared and applied as per manufacturer's specifications including preparing the surface, etc. complete. On steel work including preparing the surface after thoroughy cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.		fittings etc. complete.				
composite panel of approved make and colour for roofing at required level fixed to the GI sections. The panel should consist of 3mm thick non-halogenated FR grade mineral based polymer (2 hrs fire resistance as per ASTW E119-12 and clause B, SI, do as per ENT13501-15 and wiched between 0.50 skins thick aluminium sheet making a total panel thickness of 4mm. The surfaces will be finished with PVDF based coating on reverse sides and service coating on reverse sides would be in polyester paint. The system shall be fixed using GI brackets, aluminium L cleats/ selfthreading screws and stainless steel bolts and nuts complete with spring washer and cap muts and all other necessarys etc. Finishing with Epoxy paint (two coats) at all locations prepared and applied as per manufacturer's specifications including appropriate priming coat, preparation of surface, etc. complete. On steel work including preparing the surface after thorougly cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.	2	Providing and fixing of Aluminium	56.00	Sqm	1930.34	1 08 0
colour for roofing at required level fixed to the GI sections. The panel should consist of 3mm thick non-halogenated FR grade mineral based polymer (2 hrs fire resistance as per ASTM E119-12 and clause B, SI, do as per ENT13501-1 lsandwiched between 0.50 skins thick aluminium sheet making a total panel thickness of 4mm. The surfaces will be finished with PVDF based coating on top sides and service coating on reverse sides would be in polyester paint. The system shall be fixed using GI brackets, aluminium L cleats/ selfthreading screws and stainless steel bolts and nuts complete with spring washer and cap nuts and all other necessarys etc. Finishing with Epoxy paint (two coats) at all locations prepared and applied as per manufacturer's specifications including appropriate priming coat, preparation of surface, etc. complete. On steel work including preparing the surface after thorougly cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.		composite panel of approved make and		Jen	1000.01	1,00,0
to the GI sections. The panel should consist of 3mm thick non-halogenated FR grade mineral based polymer (2 hrs fire resistance as per ASTM E119-12 and clause B, SI, do as per ENT13501-1 sandwiched between 0.50 skins thick aluminium sheet making a total panel thickness of 4mm. The surfaces will be finished with PVDF based coating on top sides and service coating on reverse sides would be in polyester paint. The system shall be fixed using GI brackets, aluminium L cleats/ selfthreading screws and stainless steel bolts and nuts complete with spring washer and cap nuts and all other necessarys etc. Finishing with Epoxy paint (two coats) at all locations prepared and applied as permanufacturer's specifications including appropriate priming coat, preparation of surface, etc. complete. On steel work including preparing the surface after thoroughy cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.		colour for roofing at required level fixed				
consist of 3mm thick non-halogenated FR grade mineral based polymer (2 hrs fire resistance as per ASTM E1191-12 and clause B, S1, do as per ENT13501-1 lsandwiched between 0.50 skins thick aluminium sheet making a total panel thickness of 4mm. The surfaces will be finished with PVDF based coating on top sides and service coating on reverse sides would be in polyester paint. The system shall be fixed using GI brackets, aluminium L cleats/ selfthreading screws and stainless steel bolts and nuts complete with spring washer and cap muts and all other necessarys etc. Finishing with Epoxy paint (two coats) at all locations prepared and applied as per manufacturer's specifications including appropriate priming coat, preparation of surface, etc. complete. On steel work including preparing the surface after thorougly cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.		to the GI sections . The panel should				
fire resistance as per ASTM E119-12 and clause B, S1, do as per ENT/13501-1 sandwiched between 0.50 skins thick aluminium sheet making a total panel thickness of 4mm. The surfaces will be finished with PVDF based coating on top sides and service coating on reverse sides would be in polyester paint. The system shall be fixed using GI brackets, aluminium L cleats/ selfthreading screws and stainless steel bolts and nuts complete with spring washer and cap nuts and all other necessarys etc. Finishing with Epoxy paint (two coats) at all locations prepared and applied as per manufacturer's specifications including appropriate priming coat, preparation of surface, etc. complete. On steel work including preparing the surface after thoroughly cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.		consist of 3mm thick non-halogenated				
clause B, S1, do as per ENT13801-12 and clause B, S1, do as per ENT13801-15 and wiched between 0.50 skins thick aluminium sheet making a total panel thickness of 4mm. The surfaces will be finished with PVDF based coating on reverse sides would be in polyester paint. The system shall be fixed using GI brackets, aluminium L cleats/ selfthreading screws and stainless steel bolts and nuts complete with spring washer and cap nuts and all other necessarys etc. complete. Finishing with Epoxy paint (two coats) at all locations prepared and applied as per manufacturer's specifications including appropriate priming coat, preparation of surface, etc. complete. On steel work including preparing the surface after thoroughy cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.		FR grade mineral based polymer (2 hrs				
Isandwiched between 0.50 skins thick aluminium sheet making a total panel thickness of 4mm. The surfaces will be finished with PVDF based coating on top sides and service coating on reverse sides would be in polyester paint. The system shall be fixed using GI brackets, aluminium L cleats/ selfthreading screws and stainless steel bolts and nuts complete with spring washer and cap nuts and all other necessarys etc. Complete. Finishing with Epoxy paint (two coats) at all locations prepared and applied as per manufacturer's specifications including appropriate priming coat, preparation of surface, etc. complete. On steel work including preparing the surface after thoroughy cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.		The resistance as per ASTM E119-12 and				
aluminium sheet making a total panel thickness of 4mm. The surfaces will be finished with PVDF based coating on top sides and service coating on reverse sides would be in polyester paint. The system shall be fixed using GI brackets, aluminium L cleats/ selfthreading screws and stainless steel bolts and nuts complete with spring washer and cap nuts and all other necessarys etc. Complete. Finishing with Epoxy paint (two coats) at all locations prepared and applied as per manufacturer's specifications including appropriate priming coat, preparation of surface, etc. complete. On steel work including preparing the surface after thoroughy cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.		Isandwiched between 0 so cling this				
thickness of 4mm. The surfaces will be finished with PVDF based coating on top sides and service coating on reverse sides would be in polyester paint. The system shall be fixed using GI brackets, aluminium L cleats/ selfthreading screws and stainless steel bolts and nuts complete with spring washer and cap nuts and all other necessarys etc. Finishing with Epoxy paint (two coats) at all locations prepared and applied as per manufacturer's specifications including appropriate priming coat, preparation of surface, etc. complete. On steel work including preparing the surface after thorougly cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.		aluminium sheet making a total panel				
finished with PVDF based coating on top sides and service coating on reverse sides would be in polyester paint. The system shall be fixed using GI brackets, aluminium L cleats/ selfthreading screws and stainless steel bolts and nuts complete with spring washer and cap nuts and all other necessarys etc. rinishing with Epoxy paint (two coats) at all locations prepared and applied as per manufacturer's specifications including appropriate priming coat, preparation of surface, etc. complete. On steel work including preparing the surface after thoroughy cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.		thickness of 4mm. The surfaces will be				
sides and service coating on reverse sides would be in polyester paint. The system shall be fixed using GI brackets, aluminium L cleats/ selfthreading screws and stainless steel bolts and nuts complete with spring washer and cap nuts and all other necessarys etc. rinishing with Epoxy paint (two coats) at all locations prepared and applied as per manufacturer's specifications including appropriate priming coat, preparation of surface, etc. complete. On steel work including preparing the surface after thoroughy cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.		finished with PVDF based coating on top				
sides would be in polyester paint. The system shall be fixed using GI brackets, aluminium L cleats/ selfthreading screws and stainless steel bolts and nuts complete with spring washer and cap nuts and all other necessarys etc. complete. Finishing with Epoxy paint (two coats) at all locations prepared and applied as per manufacturer's specifications including appropriate priming coat, preparation of surface, etc. complete. On steel work including preparing the surface after thorougly cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.		sides and service coating on reverse				
system shall be fixed using GI brackets, aluminium L cleats/ selfthreading screws and stainless steel bolts and nuts complete with spring washer and cap nuts and all other necessarys etc. complete. Finishing with Epoxy paint (two coats) at all locations prepared and applied as per manufacturer's specifications including appropriate priming coat, preparation of surface, etc. complete. On steel work including preparing the surface after thoroughy cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.		sides would be in polyester paint. The				
aluminium L cleats/ selfthreading screws and stainless steel bolts and nuts complete with spring washer and cap nuts and all other necessarys etc. complete. Finishing with Epoxy paint (two coats) at all locations prepared and applied as per manufacturer's specifications including appropriate priming coat, preparation of surface, etc. complete. On steel work including preparing the surface after thorougly cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.		system shall be fixed using GI brackets,				
screws and stainless steel bolts and nuts complete with spring washer and cap nuts and all other necessarys etc. complete. Finishing with Epoxy paint (two coats) at all locations prepared and applied as per manufacturer's specifications including appropriate priming coat, preparation of surface, etc. complete. On steel work including preparing the surface after thoroughy cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.		aluminium L cleats/ selfthreading				
complete with spring washer and cap nuts and all other necessarys etc. complete. Finishing with Epoxy paint (two coats) at all locations prepared and applied as per manufacturer's specifications including appropriate priming coat, preparation of surface, etc. complete. On steel work including preparing the surface after thoroughy cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.		screws and stainless steel bolts and nuts				
nuts and all other necessarys etc. complete. Finishing with Epoxy paint (two coats) at all locations prepared and applied as per manufacturer's specifications including appropriate priming coat, preparation of surface, etc. complete. On steel work including preparing the surface after thoroughy cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.		complete with spring washer and cap				
Finishing with Epoxy paint (two coats) at all locations prepared and applied as per manufacturer's specifications including appropriate priming coat, preparation of surface, etc. complete. On steel work including preparing the surface after thoroughy cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.		nuts and all other necessarys etc.			7	
all locations prepared and applied as per manufacturer's specifications including appropriate priming coat, preparation of surface, etc. complete. On steel work including preparing the surface after thoroughy cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.	2	Finishing with Epoxy paint (two coats) at	1л 00		11000	
per manufacturer's specifications including appropriate priming coat, preparation of surface, etc. complete. On steel work including preparing the surface after thoroughy cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.		all locations prepared and applied as		mbo	170.00	2,04
including appropriate priming coat, preparation of surface, etc. complete. On steel work including preparing the surface after thoroughy cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.		per manufacturer's specifications				
preparation of surface, etc. complete. On steel work including preparing the surface after thoroughy cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.		77				
On steel work including preparing the surface after thoroughy cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.						
surface after thoroughy cleaning oil, grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.		Separat .				
grease, dirt and foreign matter, cost of materials, labour complete as per specifications and as per directions of Enginer-in-charge.		thorougly				
materials, labour complete as per specifications and as per directions of Enginer-in-charge.		grease, dirt and foreign matter, cost of				
specifications and as per directions of Enginer-in-charge.		materials, labour complete as per				
Enginer-in-charge.		specifications and as per directions of				
		Enginer-in-charge.				

	Rs. Total Amount Rs.
	Below the estimate amount put to quotation
	Rs.
	Above the estimate amount put to quotation.
	ADD: %(
1,60,764.26	Amount put to quotation (excluding GST) Rs. : 1,60,764.20
10000	complete

Note: GST will be reimbursed as applicable

SIGNATURE OF THE CONTRACTOR